

PANEL

| | |
|-------------------------------|---------------------------|
| Screen Size | 32" |
| Panel Technology | IPS |
| Native Resolution | 1,920 x 1,080 (FHD) |
| Brightness (nit) | 500 |
| Contrast Ratio | 1,000:1 |
| Color gamut | NTSC 72% |
| Viewing Angle (H × V) | 178 × 178 |
| Color Depth | 8bit, 16.7 Million colors |
| Response Time | 9ms (G to G) |
| Surface Treatment (Haze) | Haze 25% |
| Life time | 50,000Hrs (Min.) |
| Operation Hours (Hours / Day) | 24 / 7 |
| Portrait / Landscape | Yes / Yes |

CONNECTIVITY

| | |
|--------|----------------------------------------------------------------------------|
| Input | Digital (HDMI(2), HDCP 1.4), RS232C IN, RJ45(LAN), IR IN, USB2.0 Type A(1) |
| Output | Audio Out, USB2.0 Type B(1) |

MECHANICAL SPECIFICATION

| | |
|---------------------------------------|-------------------------|
| Bezel Color | Black |
| Bezel Width | 11.3/11.3/11.3/13.2 mm |
| Weight (Head) | 5.8 kg |
| Monitor Dimensions (W × H × D) | 723.0 x 419.4 x 39.1 mm |
| Carton Dimensions (W × H × D) | 812 x 510 x 142 mm |
| VESA™ Standard Mount Interface | 200 x 200 |

KEY FEATURE(HARDWARE)

| | |
|----------------------------------|-------------------------------------|
| Internal Memory | 8GB (System 5GB + Available 2.48GB) |
| Temperature Sensor | Yes |
| Acceleration(Gyro) Sensor | Yes |

KEY FEATURE(SOFTWARE)

| | |
|----------------------------|------------------------------------------|
| webOS ver. | webOS 6.0 |
| Embedded CMS | Local Contents Scheduling, Group Manager |
| USB Plug & Play | Yes |
| Fail over | Yes |
| Background Image | Booting Logo Image, No Signal Image |
| Video Tag | Yes |
| Play via URL | Yes |
| Screen Rotation | Yes |

| | |
|-----------------------------|----------------------------------------------------------|
| Gapless Playback | Yes |
| Setting Data Cloning | Yes |
| SNMP | Yes |
| ISM Method | Yes |
| Status Mailing | Yes |
| Control Manager | Yes |
| Cisco Certification | Yes |
| Crestron Connected | Yes |
| Power | Smart Energy Saving, PM mode, Wake on LAN, Network Ready |
| HDMI-CEC | Yes |
| SI Server Setting | Yes |
| webRTC | Yes |
| Pro:Idiom | Yes |

ENVIRONMENT CONDITIONS

| | |
|------------------------------|--------------|
| Operation Temperature | 0°C to 40°C |
| Operation Humidity | 10 % to 80 % |

POWER

| | |
|---------------------|-----------------------|
| Power Supply | AC 100-240V~, 50/60Hz |
| Power Type | Built-In Power |

POWER CONSUMPTION

| | |
|----------------------------|------------------------------------|
| Typ. | 48 W |
| Max. | 65 W |
| BTU (British Thermal Unit) | 164 BTU/Hr(Typ.), 222 BTU/Hr(Max.) |
| Smart Energy Saving (70%) | 34 W |
| DPM | 0.5 W↓ |
| Power off | 0.5 W↓ |

CERTIFICATION

| | |
|-------------------|-------------------------|
| Safety | CB / NRTL |
| EMC | FCC Class "A" / CE / KC |
| ErP / Energy Star | N/A / Yes |

SOFTWARE COMPATIBILITY

| | |
|--------------------|-----|
| SuperSign CMS | Yes |
| SuperSign Control+ | Yes |
| SuperSign Cloud | Yes |
| Mobile CMS | Yes |
| Connected Care | Yes |

ACCESSORY

